

AMENDMENTS TO THE CLAIMS

1. (Original) A vehicle accessory mount, comprising:
a body;
a pair of parallel mounting holes in the body;
a radial relief located between the parallel mounting holes; and,
a threaded accessory hole.
2. (Original) The vehicle accessory mount of Claim 1, each mounting hole further comprising:
a cylinder portion; and,
a countersink portion that is larger in diameter than the cylinder portion.
3. (Currently Amended) The vehicle accessory mount of Claim 1, further comprising:
~~whereas~~ wherein the body is generally rectangular.
4. (Currently Amended) The vehicle accessory mount of Claim 1, further comprising:
~~whereas~~ wherein the threaded accessory hole is located between the mounting holes.
5. (Currently Amended) The vehicle accessory mount of Claim 1, further comprising:
~~whereas~~ wherein the threaded accessory hole is located in substantially perpendicular relationship to the mounting holes.
6. (Original) The vehicle accessory mount of Claim 1, further comprising:
a ball stud attached to the threaded accessory hole.
7. (Original) A vehicle accessory mount, comprising:
a body;
a pair of parallel mounting holes in the body; and,
a ball stud attached to the body.

8. (Original) A vehicle accessory mount, comprising:
a body;
a pair of parallel mounting holes in the body;
a pair of hollow standoffs; and,
a threaded accessory hole.
9. (Currently Amended) The vehicle accessory mount of Claim 8, further comprising:
~~whereas~~ wherein the body is generally rectangular.
10. (Original) The vehicle accessory mount of Claim 8, the body further comprising:
a radial relief located between the parallel mounting holes.
11. (Currently Amended) The vehicle accessory mount of Claim 8, further comprising:
~~whereas~~ wherein the threaded accessory hole is located between the mounting holes.
12. (Currently Amended) The vehicle accessory mount of Claim 8, further comprising:
~~whereas~~ wherein the threaded accessory hole is located in substantially perpendicular relationship to the mounting holes.
13. (Original) The vehicle accessory mount of Claim 8, each mounting hole further comprising:
a cylinder portion; and,
a countersink portion that is larger in diameter than the cylinder portion.
14. (Currently Amended) The vehicle accessory mount of Claim 8, further comprising:
~~whereas~~ wherein the inside diameter of each hollow standoff is substantially the same as the inside diameter of the cylinder portion of the mounting holes.

15. (Original) A vehicle accessory mount, comprising:
 - a body;
 - a pair of parallel mounting holes in the body;
 - a pair of hollow standoffs; and,
 - a ball stud attached to the body.